

COOK-N-HOLD LOW TEMPERATURE SMOKER OVEN MODEL 750CHSK1EX SERIES

FEATURES AND BENEFITS:

- Fully insulated Cook-N-Hold smoker designed for flavorful results by slow cooking. Slow cooking means 15% to 20% less shrinkage. More product yield.
- Smokes with real wood chips. Cold smoke fish and cheese as well with Kold Keepers.
- Efficient 3000 Watt power unit allows for reheating of prepared meals or bulk items. Maximum temperature 350°F (176°C). Powerful 250 Watt cal rod heats chips quickly.
- Includes stainless steel vented chip box and variable timer for mild to heavy smoke flavor.
- A user-friendly solid-state control with large, high-resolution touchscreen display to ensure holding at precise food temperature.
 - 6.8", high-resolution, glove-safe, high-impact, capacitive touchscreen interface.
 - Large, easy-to-read time/temperature displays.
 - Shelf timers.
 - HACCP data collection with date/time stamp
- 6" meat probe.
- Cook and hold up to 100 lbs. (45 kg.) of meat in less than 6 sq. ft. of floor space.
- Fully insulated, stainless steel interior and exterior for ease of cleaning. Smooth interior coved corners prevent food particle/grease buildup.
- Oven is operable on either 208 or 240 Volt circuits at the flip of a switch.
- Field reversible insulated door prevents temperature loss. Silicone door gasket for proper seal. High temperature ceramic magnetic latch for "easy open" and security during transport.
- Safety conscious anti-microbial latch protect against spreading germs. Standard with right hand hinges; left hand hinging available upon request.
- Removable stainless steel pan slides have eleven positions on 1-3/8" centers. Supplied with 3 stainless steel wire grids.
- External drip pan on front keeps traffic area dry, safer.
- Heavy duty 2½" swivel casters, two with brakes. Provides mobility when fully loaded.
- Ovens can be stacked for flexibility and increased capacity.
- Cres Cor recommends soaking wood chips for a minimum of 24 hours before usage.



750CHSK1EX



- HACCP data collection with date/time stamp
- Shelf timers • Programmable recipes
- One-Touch button recipes


POWER UNIT OPTIONS:

3000 Watts, 208/240 Volts, 1 Phase, 60 Hz.
 3000 Watts, 208/240 Volts, 3 Phase, 60 Hz.
 2000 Watts, 120 Volts, 1 Phase, 60 Hz.

ACCESSORIES and OPTIONS (Available at extra cost):

- ☐ Kold Keeper®
- ☐ Stacking Kit
- ☐ Tempered Glass Door Window
- ☐ Key Lock Latch
- ☐ Extra Wire Grids
- ☐ Perimeter & Corner Bumpers
- ☐ Various Caster Options
- ☐ 120 Volt Service
- ☐ Mobile Equipment Stand 24"

750CHSK1EX Series



CRES COR MODEL NO.	PAN			DIM "A"			INSIDE DIMENSIONS			WEIGHT	
	CAP	SIZE		WIDTH	DEPTH	HEIGHT	WIDTH	DEPTH	HEIGHT	LBS	ACT.

*Additional shelves required.	9	12 X 20 X 2-1/2	IN	25-13/16	34-1/8	31-7/16	21-3/16	27	17-1/2	LBS	208
		305 X 510 X 65	MM	655	867	799	540	690	444	KG	95
	6	12 x 20 x 4	IN	<i>When adding bumpers, Add 3-11/16" to Dim "A" and 7/16" to Dim "B"</i>							
		305 x 510 x 105	MM								
	4	12 x 20 x 6	IN								
		305 x 510 x 155	MM								
	5*	18 x 26 x 1	IN								
		460 x 660 x 255	MM								

CABINET:

- Outer Body: 22 ga. stainless steel outer body.
- Inner body & top: 18 ga. stainless steel.
- Reinforcement: Internal framework of 16 ga. stainless steel.
- Insulation: Fiberglass, thermal conductivity (K factor) is .23 at 75°F, 1-1/2" in walls, 1" in doors.
- Drip pan: 18 ga. stainless steel with drain; removable.
- Wood chip box (removable): 18 ga. stainless steel; 3-5/8" L x 8" W x 2-1/4" H with 8" long handle; mounts on lower rear wall.
- Casters: 2-1/2" dia., 1-1/8" wide, swivel, load cap. 150 lbs. each, temp. range -45°/+180°F. Front casters equipped with brakes.

DOOR:

- Field reversible.
- Formed 20 ga. stainless steel.
- Latch: Anti-microbial chrome plated zinc with composite handle, ceramic magnetic type; mounted inboard.
- Hinges (2): Heavy duty chrome plated zinc; mounted inboard
- Gaskets: Perimeter type, silicone.
- Adjustable vents.

PAN SLIDES (removable):

- 18 ga. stainless steel angles, 5/8 x 1; riveted on 1-3/8" centers.
- Grids: Stainless steel, 21 x 26; supplied with (3) grids.

CLEARANCE REQUIREMENTS:

- 3" (76mm) at the back, 2" (51mm) at the top, 1" (25mm) at both sides.

ELECTRICAL COMPONENTS:

- Temperature Control with:
 - 6.8" high-resolution, glove-safe, high impact, capacitive touchscreen interface.
 - Programmable recipes
 - One-Touch button recipes
 - Shelf timers
 - HACCP data collection
 - Temperature range: 135°F (57°C) to 350°F (176°C).
- USB port with cover.
- Switch: ON-OFF rocker type
- Solid-state relay
- Power cord: Permanent, 6 ft., 12/3 ga., with right angle plug.
- Three (3) heater circuits.
- Voltage selector switch: Change to 208 or 240 Volt; on back of oven.

INSTALLATION REQUIREMENTS:

- This model complies with section 59 of UL710B for emissions of grease laden air, and according to UL is not required to be placed under a ventilation hood. Check local requirements before installation.

POWER REQUIREMENTS:

- 3000 Watts, 208/240 Volts, 60 Hz., 1 phase, 20 Amp. Service 14.4 Amps at 208 Volts, 12.5 Amps at 240 Volts.
- 3000 Watts, 208/240 Volts, 60 Hz., 3 phase, 20 Amp. Service 8.3 Amps at 208 Volts, 7.2 Amps at 240 Volts.
- 2000 Watts, 120 Volts, 60 Hz., 1 phase, 20 Amp. Service 16.6 Amps.

SHORT FORM SPECIFICATIONS

Cres Cor Insulated Under Counter Smoker Oven Model 750CHSK1EX; Solid state electronic controlled times and touchscreen temperatures. Outer body of 22 ga. stainless steel; inner body of 18 ga. stainless steel. Fiberglass insulation 1-1/2" in walls; 1" in door. Stainless steel internal frame; coved corners. Anti-microbial chrome plated latch. Three (3) heated inner walls. Smoker box and timer. Removable pan supports for (9) 12" x 20" x 2-1/2" pans spaced on 2-3/4" centers. Casters 2-1/2" swivel casters. Load capacity 150 lbs. each. 2-Year Parts / 1-Year Labor warranty. Lifetime on heating elements (excluding labor). Provide the following accessories: _____. CSA Sanitation and safety certified US & CAN.



Scan QR code
for more information
about this product.



5925 Heisley Road • Mentor, OH 44060-1833
Phone: 877/CRESCOR • Fax: 440/350-7267
www.crescor.com

© Crescent Metal Products, Inc. 2025 All rights reserved.

In line with its policy to continually improve its products, CRES COR reserves the right to change materials and specifications without notice.

Made in America Since 1936